
声 播 科 技
WAVE SOUND

Guangzhou Shengbo Technology Co., Ltd.
www.wavesound.com.cn · pt_vp@wavesound.com.cn
WhatsApp +1 508-488-9689
Engineered and tested in-house · Klippel / CLIO

CD4425

1" HF COMPRESSION DRIVER





60 W
power handling

110 dB
sensitivity (1 W / 1 m)

44.4 mm (1.7 in)
voice coil


1 kHz – 20 kHz
frequency range

FEATURES

- 44.4 mm (1.7 in) voice coil
- 25.4 mm (1 in) throat exit
- 120 mm HITACHI ferrite magnet motor
- Polymer dome diaphragm
- 110 dB, 1 W / 1 m on horn
- 100% in-line tested: frequency sweep and max-power listening check

FREQUENCY RESPONSE

1 W / 1 m



IMPEDANCE

Ω, on horn

Impedance curve ___

SPECIFICATIONS

Throat Diameter	**25.4 mm (1 in)**
Nominal Impedance	**8 Ω**
Minimum Impedance	___ Ω
DC Resistance (R_e)	___ Ω
Power Handling	
Rated[1]	**60 W**
Continuous Program[2]	**120 W**
Peak[2]	**240 W**
Sensitivity (1 W / 1 m)[3]	**110 dB**
Frequency Range[4]	**1 kHz – 20 kHz**
Recommended Crossover	**1.6 kHz (12 dB/oct)**

CONSTRUCTION

Voice Coil Diameter	**44.4 mm (1.7 in)**
Diaphragm	**Polymer dome diaphragm**
Magnet Material	**Ferrite (HITACHI)**

DIMENSIONS

Overall Diameter	**120 mm**
Depth	**55 mm**

[1] Rated power: AES standard, pink noise, 2 h, 12 dB/oct high-pass at 1.6 kHz.
[2] Program power is defined as 3 dB above the rated power; peak 4× rated.
[3] Sensitivity: 2.83 V (1 W at 8 Ω nominal), 1 m on axis, driver on horn, average 1–7 kHz.
[4] Frequency range: usable range on a suitable horn.

Full datasheet (distortion, impedance with and without horn) available on request.

Specifications subject to change without notice.